

SJS



D 25 RT

D 25 AC

D 25 RF

D 25 PX

AL 450

TA 450

TA 700



YANMAR
22 KW
(30 HP)

YANMAR
22 KW
(30 HP)

YANMAR
22 KW
(30 HP)

YANMAR
22 KW
(30 HP)

YANMAR
36 KW
(48 HP)

YANMAR
36 KW
(48 HP)

PERKINS
47 KW
(63 HP)



Idrostatica
automotive 4x4

Idrostatica
automotive 4x4

Idrostatica
automotive 4x4

Idrostatica
automotive 4x4

Idrostatica
automotive 4x4

Idrostatica
automotive 4x4

Idrostatica
automotive 4x4



R.MIN. 2350 mm
R.MAX. 3650 mm

R.MIN. 2350 mm
R.MAX. 3650 mm

R.MIN. 2350 mm
R.MAX. 3650 mm

R.MIN. 2350 mm
R.MAX. 3650 mm

R.MIN. 1600 mm
R.MAX. 3020 mm

R.MIN. 1600 mm
R.MAX. 3336 mm

R.MIN. 1900 mm
R.MAX. 3950 mm



A= 1590 mm
B= 2465 mm
C= 3320 mm

A= 1590 mm
B= 2465 mm
C= 3320 mm

A= 1590 mm
B= 2465 mm
C= 3320 mm

A= 1590 mm
B= 2465 mm
C= 3015 mm

A= 1450 mm
B= 2450 mm
C= 4140 mm

A= 1450 mm
B= 2460 mm
C= 4200 mm

A= 1780 mm
B= 2690 mm
C= 5200 mm



I= 9 Km/h
II= 20 Km/h

I= 9 Km/h
II= 20 Km/h

I= 9 Km/h
II= 20 Km/h

I= 9 Km/h
II= 20 Km/h

I= 11 Km/h
II= 24 Km/h

I= 11 Km/h
II= 24 Km/h

I= 10 Km/h
II= 30 Km/h



2020 Kg.

2020 Kg.

2270 Kg.

1670 Kg.

3100 Kg.

3100 Kg.

4850 Kg.



1000 l. min.
1350 l. max.
2500 Kg.

1000 l. min.
1450 l. max.
2300 Kg.

1000 l. min.
1450 l. max.
2300 Kg.

500 l. min.
650 l. max.
870 Kg.

500 l.
2000 Kg.

500 l.
2000 Kg.

720 l.
3200 Kg.



3000 mm

3600 mm

SLIM

SLIM